



THE ODISHA STATE POLICE HOUSING & WELFARE CORPORATION LTD.

(A Government of Odisha Undertaking)

JANAPATH, BHONINAGAR, BHUBANESWAR-22.

Ph:0674-2541545,2542921,Fax:0674-2541543

Email:ophwc.od@nic.in, Website:www.ophwc.nic.in

EoI No.- 03/SE/EOI/2019-20

EXPRESSION OF INTEREST

Odisha State Police Housing & Welfare Corporation invites Expression of Interest (EoI) from registered Manufacturers/Distributors /Authorized dealer /Agencies having experience in supplying & fixing of kitchen equipments of reputed and popular make for Kitchen-cum-Dinning (200 capacity) at UPTTI, Bhubaneswar. For overview of the bidding terms and conditions, scope of work, pre-qualification criteria, etc., please go through the documents available in our website www.ophwc.nic.in. Interested Parties/Vendors who meet the pre-qualification criteria may download the tender documents from the website and submit the same with a covering letter duly signed by an authorized signatory and a non-refundable cost of bid documents of Rs. 7080.00/- (Rupees Seven thousand eighty only) in the form of a Demand draft or a Pay Order (drawn in favour of The Odisha State Police Housing & Welfare Corporation, payable at Bhubaneswar) on or before by 3.00 PM Dt 30/03/2020 at the following address: G.M. (Tech.) – cum - SE, Odisha State Police Housing & Welfare Corporation, Bhoinagar, Janpath, Bhubaneswar, Pin:- 751022.

All Addendums/Corrigendum's to this notice if required shall be issued on the above said web site of the Corporation only.

Sd/-

**G.M. (Tech.) – cum - SE
OSPH& WC, Bhubaneswar**

Any query in the matter may please be got clarified from the contact person stated below-

1. Sri. B.R Bhola, APM - 9438447266
2. Sri. R.S Patnaik, DGM - 9637118483

BIDDERS INFORMATION

Sl No	Particulars	Information	Remarks
1	Name of the organization		
2	Type of Organization Whether Proprietorship, Partnership etc. (Please enclose related documents)		
3	Name of the Proprietor/ Partners/ Directors		
4	Details of Registration (Firm, Company etc.) (Registering Authority, Date, Number etc.)		
5	Experience in the respective field of work		
6	a) Registered office address and telephone no.		
7	Office address through which the work will be handled		
8	Details of Manpower available		
9	Indicate whether the firm has any disputes/ litigation with other customers.		
9	Any other relevant information		

Sign of the Bidder

LIST OF DOCUMENTS ENCLOSED

Sl No	Document	Complied (Yes/No)	Page No
1	Bid Form, duly filled in, as per Tender Document		
2	Cost of bid document in the form of DD with details.		
3	The copy of Experience certificate as per NIT		
4	Authenticated certificate to ascertain the turn over and work experience of the bidder duly certified by Chartered Accountant and/or valid IT returns.		
5	Technical Bid (Part-A) and Financial Bid (Part-B) Duly Sealed as required		
6	Original Catalogues of products and authorization		
7	Affidavit regarding no dispute/ litigation with other agencies/ customers		
8	Time period for Supply		
9	Any other relevant documents (Details to be indicated)		
10	EMD as DD/Pay Order as required in the NIT		

Sign of the bidder

FORM OF DECLARATION

I/ WE agree

- a) To provide true and correct information to the Odisha State Police Housing & Welfare Corporation and I declare that all information I provide in the EoI is true and correct.
- b) That I accept these Terms and Conditions, including acceptance of any changes to the Terms and Conditions.
- c) That I am responsible for accessing and reading correspondence, notices and information provided by the Odisha State Police Housing & Welfare Corporation on the website and that the Corporation may assume that I have accessed and read any such correspondence, notices and information relating to this EoI.
- d) That I consent to disclosure of my information provided on this Expression of Interest including information in relation to skills, employment, etc. except Financial Bid.
- e) That the Odisha State Police Housing & Welfare Corporation is not liable for the consequences that may arise due to incomplete or inaccurate information provided by me in the EoI documents.

Sign of the Bidder

SCOPE OF WORK: Supply & Fixing of Kitchen equipment's for Kitchen-cum-Dinning (200 capacity) at UPTTI, Bhubaneswar.

ITEM No.	DESCRIPTION OF ITEM	Qty in Nos. (Approx.)
3 BURNER INDIAN RANGE WITH 1 U/S	<p>Size : - 72"x24"x34" Front – 18 Gauge 304 SS Sides – 20 Gauge 304 SS Top – 16 Gauge 304 SS Burners – M – 66 with drip trays and pilot lamp . The unit to be mounted on nylon bullet type adjustable feet .</p>	1
TABLE CHAMBER DEEP FAT FRY	<p>Size : - 24"x24"x34"+6" Front – 18 Gauge 304 SS Sides – 20 Gauge 304 SS Top – 16 Gauge 304 SS</p>	1
WORK TABLE WITH 2 U/S	<p>Size:-48"X24"X34"+6" SS Sheet 304 Grade Top : 16 SWG SS Legs : 16 SWG SS Pipes SS Shelves: 18 SWG 304 Grade SS. The unit is to be mounted on bullet type adjustable feet .</p>	1
PICKUP TABLE WITH 2 U/S AND OHS	<p>Size :- 60"x30"x34" +18"+12" Top : 16 SWG 304 Grade SS Legs : 16 SWG SS Pipes 304 Grade Shelves : 18 SWG 304 Grade SS. . The unit is to be mounted on bullet type adjustable feet .</p>	1
SINK WITH BUTCHARY TABLE WITH 1 U/S	<p>Size: 72"x24"x34"+6" Top : 16 SWG SS 304 Grade Legs: 16 SWG SS Pipes. The unit is to be mounted on bullet type adjustable feet. Sink to Under Self</p>	1
WATER COOLER WITHPURIFAIR	<p>CAPACITY:60 LtrsStorage water coolers specially designed for schools, colleges, canteens, offices, factories, public places and other corporate & commercial applications.Celfrost is a name synonymous with quality and reliability which now brings to you refreshing water coolers with a wide range of capacities and features for every need.230v/1PH/ 50Hz Supply</p>	1

TWO DOOR UNDER COUNTER WORK TOP FREEZER WITH OHS	Size: 66"X 30"X34"+18"+12" compressor to be fitted CAPACITY: 500Ltr	1
WORKING TABLE WITH 2 U/S	Size: 60"X24"X34" SS Sheet 304 Grade Top : 16 SWG SS Legs : 16 SWG SS Pipes SS Shelves: 18 SWG 304 Grade SS. The unit is to be mounted on bullet type adjustable feet.	2
BULK COOKING STOCK POT	Size :- 30"x30"x24" Front – 18 Gauge 304 SS Sides – 20 Gauge 304 SS Top – 16 Gauge 304 SS Burners – M – 66 with drip trays and pilot lamp. The unit to be mounted on nylon bullet type adjustable feet	3
TWO DOOR VERTICAL DEEP CHILLER	Size:-30"X28"X80" ISI mark compressor to be fitted CAPACITY: 500Ltr	1
TWO DOOR VERTICAL DEEP FREEZER	Size:-30"X28"X80" ISI mark compressor to be fitted CAPACITY: 500Ltr	1
IDLY STEAMER	CAPACITY:96 Pic 304 Grade SS, Electric Systemwith thermostat	1
CHAPATI HOT PLATE WITH PUFFER	Size:- 42"X24"X34" 304 Grade BURNER – RV 2 ft. with drip trays and pilot lamp. Puffer- 1FtTop – MS Plate 16 MSLegs – 16 SWG SS Pipes	1
CHAPATI ROLLING TABLE WITH GRANITE TOP 2 U/S	Size: 48"X30"X34" SS Sheet 304 Grade Top : 16 SWG SS Legs : 16 SWG SS Pipes SS Shelves: 18 SWG 304 Grade SS. The unit is to be mounted on bullet type adjustable feet.	1

FOOD SERVING VEG COUNTER	SIZE:- 66"X30"X34" Tank construction in 22 SWG thick S.S sheet 304 Grade immersion type. Heating elements quick acting ball valve for BAIN MARIE Drain off water inlet faucet / socket glass wool insulation 22 SWG thick S.S sheet. front grill for plate serving Watt:-1.5 kw heater	1
NON-VEG SERVINGCOUNTER	SIZE:- 36"X30"X34" Tank construction in 22 SWG thick S.S sheet 304 Grade immersion type. Heating elements quick acting ball valve for BAIN MARIE Drain off water inlet faucet / socket glass wool insulation 22 SWG thick S.S sheet. front grill for plate serving Watt:-1.5 kw heater	1
DOUGH KNEEDER	Capacity: 25 Kg. Duration:-15min Material: Stainless Steel Structure Hand Held, Table Voltage(V)220vPower(W) 3.2kW We are listed amongst prominent manufacturers and suppliers of Dough Maker in the market. Our offered products are technically manufactured using the best quality raw material available in the market.	1
TILTING TYPE WET GRINDER	Capacity: 15 ltr Material Grade SS: 304 Body Made of 16 SWG sheet food gr. Complete with revolving drum, grinding stone Cycle 8-10 min/cycle Motor: 1 hp Motor Brand Crompton	1
POTATO PEELER	Capacity :- 10 kg Material Grade SS: 304 Body Made of 16 SWG sheet food gr. Complete with revolving drum, Cycle 8-10 min/cycle Motor: 1 hp Motor Brand Crompton	1

POT RACK	Size:- 48"X30"X66" 4 SHELVES Heavy duty SS round pipe frame fabricated. SS angle verticals with nylon bullet adjustable	1
CLEANING DISH LANDING TABLE WITH OHS	Size:- 72"X24"X34" Top : 16 SWG 304 Grade SS Legs : 16 SWG SS Pipes 304 Grade Shelves: 18 SWG 304 Grade SS. With 1 Under shelves . The unit is to be mounted on bullet type adjustable feet. GARBAGE CHUTE	2
3 SINK UNIT	Size:- 60"X24"X34"+6" Top, Flash Back & Drain Board 16 SWG SS Sheet 304 Grade. Under Frame: Heavy duty SS angle. SINK: Sinks will be constructed of 16 SWG, 304 grade LEGS: Heavy duty	1
DISH RACK/GLASS/PLATE RACK	Size:- 44"X18"X66" 4 SHELVES 304 Grade Top : 16 SWG SS Legs: 16 SWG SS Pipes. The unit is to be mounted on bullet type adjustable feet.	1
EXHAUST HOOD FOR 3 BURNER WITH FILTER	Size:- 78"X30"X18" 22 Gauge SS. wall mounted cantilever type Hoods including SS baffle type washable grease filters 2" thick with 22 Gauge frame.	1
EXHAUST HOOD FOR DEEP FRYER WITH FILTER	Size:- 30"X30"X18" 22 Gauge SS. wall mounted cantilever type Hoods including SS baffle type washable grease filters 2" thick with 22 Gauge frame.	1
EXHAUST HOOD FOR STOCK POT WITH FILTER	Size:- 36"X30"X18" 22 Gauge SS. wall mounted cantilever type Hoods including SS baffle type washable grease filters 2" thick with 22 Gauge frame.	3
EXHAUST HOOD FOR CHAPATI HOT PLATE WITH FILTER	Size:- 48"X30"X18" 22 Gauge SS. wall mounted cantilever type Hoods including SS baffle type washable grease filters 2" thick with 22 Gauge frame.	1

EXHAUST AIR DUCTING	24 Gauge G.I ducting includingFabrication, erection and commissioning with offsets, elbows cowls, felts hangers, bird screen, and anchor fasteners with G.I nut and bolts. AS PER ACTUAL Sqft FOR (EXHAUST AIR)	1200
FRESH AIR DUCTING	24 Gauge G.I ducting includingFabrication, erection and commissioning with offsets, elbows cowls, felts hangers, bird screen, and anchor fasteners with G.I nut and bolts. AS PER ACTUAL Sqft(FRESH AIR)	865
GAS PIPELINE	GAS PIPE LINE CONECTION ONE SET WITH 5 POINT X2 MAIFOLD WITH all accessories The pipe shall be of MS Seamless Scheduleor TATA 'C' class ERW Pipe . The main pipeline should be of ½” dia with respective ball valve. The pipeline should have seamless schedule pipe fittings such as Tee,Elbow and other fittings up to ½” dia and the pipe from ½” dia should be hydraulically bent. There should be two numbers of manifold (each with the specified number of cylinder adaptors) made of seamless schedule 40 pipes with required fittings like NRV, cylinder adaptor (click on type) with flexible pipe of 2’ . There should be a isolation ball valve in both the manifold to operate the manifold individually .There should be a main gas shut off valve inside and outside the gas bank to isolate the LPG supply in case emergency . The main pipeline should run up to the Kitchen area and from there it will be distributed to all the the kitchen equipments with a 2nd stage regulator . There should be a pressure gauge with a needle control valve installed inside the kitchen . The entire gas pipe line should be clamped properly with MS clamps on the wall .Once the entire pipe line is completed the same needs to be pressure	1

	tested 2 manifolds of 5 cylinders each.	
EXHAUST FAN	<p>Size:-18" Almonard Industrial Heavy Duty Exhaust Fan 1440 RPM, 1PH MOTOR</p> <p>Totally enclosed, continuously rated motor Every Almonard Exhaust Fan features a capacitor star and run type motor continuously rated, totally enclosed and ruggedly built. Designed specifically for the purpose, the motor has prelubricated double ball bearing and is provided with Class "A" and "E" insulation. The end result is a smooth, silent motor that lasts longer and deliver the maximum output at lower operating cost.Dynamically Balanced ImpellerThe impeller used in an ALmonard Exhaust Fan is of the propeller type and since both hub and impeller are dynamically balances and frames and arms mounted on rubber bushing, vibration are virtually eliminated.</p> <p>With installation</p>	3
EXHAUST FAN	<p>Size:- 15" Almonard Industrial Heavy Duty Exhaust Fan 1440 RPM, 1PH MOTOR</p> <p>Totally enclosed, continuously rated motor Every Almonard Exhaust Fan features a capacitor star and run type motor continuously rated, totally enclosed and ruggedly built. Designed specifically for the purpose, the motor has prelubricated double ball bearing and is provided with Class "A" and "E" insulation. The end result is a smooth, silent motor that lasts longer and deliver the maximum output at lower operating cost.Dynamically Balanced ImpellerThe impeller used in an ALmonard Exhaust Fan is of the propeller type and since both hub and impeller are dynamically balances and frames</p>	2

	<p>and arms mounted on rubber bushing, vibration are virtually eliminated.</p> <p>With installation</p>	
AIR CURTAIN	<p>Size: 48" (L) Air Curtain is an environment, separation equipment which prevents outside air, insects and hot air entry to the conditioned area through the open door ways or the door being opened at frequent intervals. The principal of Air Curtain is that it blows the atmosphere air to constant velocity at the doorways and forms a Air stream for the entire width and height of the door openings. The velocity will vary depending on the effective throw of the air stream. Moreover, you can reduce your energy consumption considerably by holding the uniform cold air temperature at the air conditioned area. In Total it is an energy conservation unit for the air conditioned area. It also eliminated the flies and other small insects infiltration through an open door in order to maintain the required hygienic standard in the specified areas. Our commitment to quality at economical Rates had made millions to provide comfortable environment in their establishments. 1400 RPM, 1.5 HP MOTOR, 180Watt</p>	2
INSECT KILLER	<p>DOUBLE TUB Dimension (cm): lxbxh - 65x10.8X30.3 8, 000 Hour lamp life with a high powered killing grid Wall mounted or no standing - hanging chain included Removable catchment tray for dead insect bodies, easily cleanable without insect contact, Electric power: 39 watts / bulbs: philips tubes 2 pcs 18 watt blue colour uv bulbs (replaceable)</p>	2

FRESH AIR VENT DIFFUSER	Size:-15"X6" ADJUSTABLE GRILLES This is the most common type of grille used as a supply outlet with adjustable vanes to provide multi directional air flow. Made out of extruded aluminium section and available in powder coated/anodised finish.	10
------------------------------------	---	-----------

PRE-QUALIFICATION CRITERIA& TERMS AND CONDITIOS

A. TECHNICAL REQUIREMENTS

1. The applicant should be a well-established specialized agency having experience in Supply and installation of Kitchen equipment's for Kitchen-cum-Dinning Hall in Govt. or Private Institution.
2. The applicant should have at least 03 years experience in similar nature of work and they have executed one work of not less than Rs. 20 lakh in one year or Rs. 12 lakh in each case for 2 or more works or Rs 8 lakh in each case for 3 or more work in a year. Experience should be documented in the form of work completion certificate signed by an officer not below the level of Executive Engineer/ Head of the Institution of the employer. Submission of Work Order in place of experience certificate will not be acceptable.
3. Un-attested documents shall not be treated as a valid document for the purpose of evaluation.
4. The bidders should have applicable Tax registrations (GST, PAN) and other requisite government clearances that are necessary for such work.
5. (a) The firm should have a minimum turnover of Rs. 45 Lakhs during each of the last three financial years. Documentary proof of the same as audited financial statement and IT returns should be submitted.
(b) The firm must have a Registered Branch office or authorised distributor available in Odisha.
6. The bidder/firm should be free from any litigation/ Court cases and should not have been debarred from execution in last three years. An affidavit in this regard should be submitted.
7. Agencies not fulfilling the minimum eligibility criteria shall be summarily rejected.
8. The OSPHWC can ask for more clarifications, documents, samples of products (Not mentioned in this EOI) from the bidders as & when required for technical evaluation of credentials of the bidder.
9. Required test certificate conforming to IS Standard / manufacturer test certificate for materials used need to be furnished.
10. The bidder should possess ISO 9001-2015, ISO 4901-2015, ISO 8001-2004, BIFMA & Green Guard certificate for the products supplied.

B. OTHER TERMS AND CONDITIONS

1. The proposal and all correspondence and documents shall be written in English.
2. **Mode of receipt of tender form :**
 - a) Tender document can be downloaded from the Corporation's website www.ophwc.nic.in containing all details of items and terms & conditions. The bidder will submit the non-refundable cost of bid document of Rs 7,080/- separately and a refundable bid security of Rs 24000/- (Twenty Four Thousand Only) in the form of bank DD payable at Bhubaneswar in the name of Odisha State Police Housing and Welfare Corporation Ltd.
 - b) The technical bid of the tenders shall be opened at 16.30 hrs on the closing day in the Corporate Office of the Corporation at Bhubaneswar in presence of bidders or their authorized agents
 - c) The bid shall be submitted in two parts: -
 - i). **Part A: - TECHNICAL BID** – It will consists of the company/ establishment profile indicating the capability, experience as mentioned for eligibility, Financial turnover bid security and cost of bid document as per NIT. This sealed envelope will be marked as “ PART-A, TECHNICAL BID”.
 - ii) **Part II: - FINANCIAL BID** – It will contain the price of the tender items. This sealed envelope shall be marked as “ PART-B, FINANCIAL BID”
 - iii) The envelope of part-A & part B together shall be sealed in another envelope marked as **EoI for supply & Installation of kitchen equipments for kitchen-cum-dinning hall at UPTTI, Bhubaneswar.**

3. Rates to Include:

While quoting their rates, the bidder should include the following also, if otherwise not stated herein before.

- a) Contractor may make suitable provisions for meeting all tender obligations as per document such as transport cost, insurance, overheads, supply & fixing charges etc and also consider trade discount available to him from manufacturer or dealer and quote the rates against each item accordingly.
- b) Rates should include all expenses except GST as per Act, etc. and should be valid for the entire Contract period. No escalation of rates will be allowed for the entire contract period on any account. GST to be indicated separately.
- d) Rates for supply & Installation of kitchen equipments for kitchen-cum-dinning hall should include cost of all materials, labour, cess, royalty and all other statutory and incidental charges for completion of the works at the location.
- e) Rates offered for supply & supply & Installation of kitchen equipment's for kitchen-cum-dining hall should include cost of all materials, carriage charges for landing at the site with labour, cess, royalty and all other statutory and incidental charges. It will be the responsibility of the bidder to transport the material to the concerned locations and supply & fixing at proper place at their own cost & risk.
- f) The quoted rate shall include the cost of all minor/sundry items to make it functional.

4 QUANTITY OF WORK TO BE EXECUTED

The Schedule of Quantities, unless otherwise stated, shall be deemed to have been prepared in accordance with the Standard Procedure and shall be considered to be approximate and subject to variation. The Employer reserves the right to execute only a part or the whole or any excess or less thereof without assigning any reason therefore.

- 5 Bidders are requested to attach original product brochures and authorization letters.
- 6 The bids of those who qualifies in the technical evaluation of Part-A only shall be opened for evaluation of financial criteria.
- 7 Intending bidders/ agencies not meeting the minimum eligibility criteria shall be summarily rejected and their financial offers will not be opened.

- 8 Evaluation: A committee appointed by the competent authority of OSPHWC shall evaluate the Part-A bid first and thereafter, PART-B envelopes of those of bidders who qualified in the technical evaluation shall be opened for financial evaluation.
9. The interested agencies may visit the actual site for getting necessary details.
10. **Locations of Work and quantum:** UPTTI, Bhubaneswar.
11. Technically selected agencies may, if feels necessary by the authority of the OSPHWC, be called for making a presentation at the HO of the Corporation at the date and time fixed by it. The presentation should clearly spell out following points:
 - a) Brief history and financial strength (turn over) of the company and Similar work already executed.
 - b) The representatives of agency will give details presentations regarding his planning for completing the work within the scheduled time, if placed with work order.
 - c) Design considerations including optimized utilization of available rooms along with suggestions for improvements for the work, for achieving better performance of the facility. Such information shall be based on the vendor's completed work experience and meeting all the norms and regulations.
 - d) Brief description, specifications of materials, the source of materials etc will be presented by the agency.
12. Before execution of the agreement, the selected firm shall deposit Performance Security (2% of the value of work order) in shape of Demand Draft drawn in favor of Odisha State Police Housing & Welfare Corporation, payable at Bhubaneswar.
13. Period of completion / Time limit for completion of work shall be 30 days from issuance of work order.
14. Any shifting of debris in the place of work will be carried out by the agency without additional cost.
15. While deciding upon the selection of contractor, emphasis will be given on the ability and competence to do good quality of work in accordance with the specifications and within the time. The OSPHWC shall consider placement of orders on those eligible bidders /bidders whose offers have been found technically, commercially and financially acceptable. The Corporation also reserves the right to split the contract and award to two or more bidders, if it feels expedient to do so, provided the L2/L3 bidder match the rates offered by the L1 bidder.
16. The OSPHWC reserves the right to accept or reject any bid, and to annul the bidding process and reject all bids, at any time prior to award of contract without assigning any reason whatsoever and without thereby incurring any liability to the affected bidder or bidders on the grounds of the action of the Corporation.
17. Payment shall be made on 100% completion of work against a particular work order. At no point of time running payment shall be made. For the purpose of this clause, each location shall be considered as a single work.
18. The work will be accepted as completed, only after quality assurance tests/checks are carried out by inspecting authority of the OSPHWC.
19. The issue of Work Order shall constitute the award of contract on the bidder. The successful bidder shall sign an agreement in non-judicial stamp paper of Rs 100/- with the Corporation before issue of Work Order.
20. The OSPHWC or its representative shall have the right to inspect and test the goods and works, during execution and before accepting it as completed as per prescribed test schedules for their conformity to the specifications. Should any inspected or tested goods fail to conform to the Specifications, the Corporation may reject them

and the contractor shall either replace the rejected goods or make all alterations necessary to meet Specification requirements at their own cost

21. Any dispute shall be subject to the jurisdiction of Hon'ble High Court of Odisha.
22. Bidders are responsible for any defects for 5 years from the date of handing over of the work, which shall be rectified conforming to the specification and those beyond rectification should be replaced free of cost.

**G.M. (Tech.) – cum – S.E.,
OSPH&WC, Bhubaneswar**

Sign of Bidder

PART- B FINANCE BID

Sl. No	Items	DESCRIPTION OF ITEM	Unit	Rate Per Unit (in figures)	Rate per unit (In words)
1	3 BURNER INDIAN RANGE WITH 1 U/S	Size : - 72"x24"x34" Front – 18 Gauge 304 SS Sides – 20 Gauge 304 SS Top – 16 Gauge 304 SS Burners – M – 66 with drip trays and pilot lamp . The unit to be mounted on nylon bullet type adjustable feet .			
2	TABLE CHAMBER DEEP FAT FRY	Size : - 24"x24"x34"+6" Front – 18 Gauge 304 SS Sides – 20 Gauge 304 SS Top – 16 Gauge 304 SS			
3	WORK TABLE WITH 2 U/S	Size:-48"X24"X34"+6" SS Sheet 304 Grade Top : 16 SWG SS Legs : 16 SWG SS Pipes SS Shelves: 18 SWG 304 Grade SS. The unit is to be mounted on bullet type adjustable feet.			
4	PICKUP TABLE WITH 2 U/S AND OHS	Size :- 60"x30"x34"+18"+12" Top : 16 SWG 304 Grade SS Legs : 16 SWG SS Pipes 304 Grade Shelves : 18 SWG 304 Grade SS. . The unit is to be mounted on bullet type adjustable feet .			
5	SINK WITH BUTCHARY TABLE WITH 1 U/S	Size: 72"x24"x34"+6" Top : 16 SWG SS 304 Grade Legs: 16 SWG SS Pipes. The unit is to be mounted on bullet type adjustable feet. Sink to Under Self			
6	WATER COOLER WITHPURIFAIR	CAPACITY:60 LtrsStorage water coolers specially designed for schools, colleges, canteens, offices, factories, public places and other corporate & commercial applications.Celfrost is a name synonymous with			

		quality and reliability which now brings to you refreshing water coolers with a wide range of capacities and features for every need.230v/1PH/ 50Hz Supply			
7	TWO DOOR UNDER COUNTER WORK TOP FREEZER WITH OHS	Size: 66"X 30"X34"+18"+12" compressor to be fitted CAPACITY: 500Ltr			
8	WORKING TABLE WITH 2 U/S	Size: 60"X24"X34" SS Sheet 304 Grade Top : 16 SWG SS Legs : 16 SWG SS Pipes SS Shelves: 18 SWG 304 Grade SS. The unit is to be mounted on bullet type adjustable feet.			
9	BULK COOKING STOCK POT	Size :- 30"x30"x24" Front – 18 Gauge 304 SS Sides – 20 Gauge 304 SS Top – 16 Gauge 304 SS Burners – M – 66 with drip trays and pilot lamp. The unit to be mounted on nylon bullet type adjustable feet			
10	TWO DOOR VERTICAL DEEP CHILLER	Size:-30"X28"X80" compressor to be fitted CAPACITY: 500Ltr			
11	TWO DOOR VERTICAL DEEP FREEZER	Size:-30"X28"X80" compressor to be fitted CAPACITY: 500Ltr			
12	IDLY STEAMER	CAPACITY:96 Pic 304 Grade SS, Electric Systemwith thermostat			
13	CHAPATI HOT PLATE WITH PUFFER	Size:- 42"X24"X34" 304 Grade BURNER – RV 2 ft. with drip trays and pilot lamp. Puffer- 1FtTop – MS Plate 16 MSLegs – 16 SWG SS Pipes			
14	CHAPATI ROLLING TABLE WITH GRANITE TOP 2 U/S	Size: 48"X30"X34" SS Sheet 304 Grade Top : 16 SWG SS Legs : 16 SWG SS Pipes SS Shelves: 18 SWG 304 Grade SS. The unit is to be mounted on Nylon bullet type adjustable feet.			

15	FOOD SERVING VEG COUNTER	SIZE:- 66"X30"X34" Tank construction in 22 SWG thick S.S sheet 304 Grade immersion type. Heating elements quick acting ball valve for BAIN MARIE Drain off water inlet faucet / socket glass wool insulation 22 SWG thick S.S sheet. front grill for plate serving Watt:-1.5 kw heater			
16	NON-VEG SERVINGCOUNTER	SIZE:- 36"X30"X34" Tank construction in 22 SWG thick S.S sheet 304 Grade immersion type. Heating elements quick acting ball valve for BAIN MARIE Drain off water inlet faucet / socket glass wool insulation 22 SWG thick S.S sheet. front grill for plate serving Watt:-1.5 kw heater			
17	DOUGH KNEEDER	Capacity: 25 Kg. Duration:-15min Material: Stainless Steel Structure Hand Held, Table Voltage(V)220vPower(W) 3.2kW We are listed amongst prominent manufacturers and suppliers in the market. Our offered products are technically manufactured using the best quality raw material available in the market.			
18	TILTING TYPE WET GRINDER	Capacity: 15 ltr Material Grade SS: 304 Body Made of 16 SWG sheet food gr. Complete with revolving drum, grinding stone Cycle 8-10 min/cycle Motor: 1 hp Motor Brand Crompton			
19	POTATO PEELER	Capacity :- 10 kg Material Grade SS: 304 Body Made of 16 SWG sheet food gr. Complete with revolving drum, Cycle 8-10 min/cycle Motor: 1 hp Motor Brand Crompton			

20	POT RACK	Size:- 48"X30"X66" 4 SHELVES Heavy duty SS round pipe frame fabricated. SS angle verticals with nylon bullet adjustable			
21	CLEANING DISH LANDING TABLE WITH OHS	Size:- 72"X24"X34" Top : 16 SWG 304 Grade SS Legs : 16 SWG SS Pipes 304 Grade Shelves: 18 SWG 304 Grade SS. With 1 Under shelves . The unit is to be mounted on bullet type adjustable feet. GARBAGE CHUTE			
22	3 SINK UNIT	Size:- 60"X24"X34"+6" Top, Flash Back & Drain Board 16 SWG SS Sheet 304 Grade. Under Frame: Heavy duty SS angle. SINK: Sinks will be constructed of 16 SWG, 304 grade LEGS: Heavy duty			
23	DISH RACK/GLASS/PLATE RACK	Size:- 44"X18"X66" 4 SHELVES 304 Grade Top : 16 SWG SS Legs: 16 SWG SS Pipes. The unit is to be mounted on Nylon bullet type adjustable feet.			
24	EXHAUST HOOD FOR 3 BURNER WITH FILTER	Size:- 78"X30"X18" 22 Gauge SS. wall mounted cantilever type Hoods including SS baffle type washable grease filters 2" thick with 22 Gauge frame.			
25	EXHAUST HOOD FOR DEEP FRYER WITH FILTER	Size:- 30"X30"X18" 22 Gauge SS. wall mounted cantilever type Hoods including SS baffle type washable grease filters 2" thick with 22 Gauge frame.			
26	EXHAUST HOOD FOR STOCK POT WITH FILTER	Size:- 36"X30"X18" 22 Gauge SS. wall mounted cantilever type Hoods including SS baffle type washable grease filters 2" thick with 22 Gauge frame.			
27	EXHAUST HOOD FOR CHAPATI HOT PLATE WITH FILTER	Size:- 48"X30"X18" 22 Gauge SS. wall mounted cantilever type Hoods including SS baffle type washable grease filters 2"			

		thick with 22 Gauge frame.			
28	EXHAUST AIR DUCTING	24 Gauge G.I ducting includingFabrication, erection and commissioning with offsets, elbows cowls, felts hangers, bird screen, and anchor fasteners with G.I nut and bolts. AS PER ACTUAL Sqft FOR (EXHAUST AIR)			
29	FRESH AIR DUCTING	24 Gauge G.I ducting includingFabrication, erection and commissioning with offsets, elbows cowls, felts hangers, bird screen, and anchor fasteners with G.I nut and bolts. AS PER ACTUAL Sqft(FRESH AIR)			
30	GAS PIPELINE	GAS PIPE LINE CONECTION ONE SET WITH 5 POINT X2 MAIFOLD WITH all accessories The pipe shall be of MS Seamless Schedule or TATA 'C' class ERW Pipe . The main pipeline should be of ½" dia with respective ball valve. The pipeline should have seamless schedule pipe fittings such as Tee,Elbow and other fittings up to ½" dia and the pipe from ½" dia should be hydraulically bent. There should be two numbers of manifold (each with the specified number of cylinder adaptors) made of seamless schedule 40 pipes with required fittings like NRV, cylinder adaptor (click on type) with flexible pipe of 2' . There should be a isolation ball valve in both the manifold to operate the manifold individually .There should be a main gas shut off valve inside and outside the gas bank to isolate the LPG supply in case emergency . The main pipeline should run up to the Kitchen area and from there it will be distributed to all the the kitchen equipments with a 2nd stage regulator . There should be a pressure gauge with a needle control valve installed inside the kitchen . The entire gas pipe line should be clamped properly with MS clamps on the			

		wall .Once the entire pipe line is completed the same needs to be pressure tested 2 manifolds of 5 cylinders each.			
31	EXHAUST FAN	<p>Size:-18" Almonard Industrial Heavy Duty Exhaust Fan 1440 RPM, 1PH MOTOR</p> <p>Totally enclosed, continuously rated motor Every Almonard Exhaust Fan features a capacitor star and run type motor continuously rated, totally enclosed and ruggedly built. Designed specifically for the purpose, the motor has prelubricated double ball bearing and is provided with Class "A" and "E" insulation. The end result is a smooth, silent motor that lasts longer and deliver the maximum output at lower operating cost.Dynamically Balanced ImpellerThe impeller used in an ALmonard Exhaust Fan is of the propeller type and since both hub and impeller are dynamically balances and frames and arms mounted on rubber bushing, vibration are virtually eliminated.</p> <p>With installation</p>			
32	EXHAUST FAN	<p>Size:- 15" Almonard Industrial Heavy Duty Exhaust Fan 1440 RPM, 1PH MOTOR</p> <p>Totally enclosed, continuously rated motor Every Almonard Exhaust Fan features a capacitor star and run type motor continuously rated, totally enclosed and ruggedly built. Designed specifically for the purpose, the motor has prelubricated double ball bearing and is provided with Class "A" and "E" insulation. The end result is a smooth, silent motor that lasts longer and deliver the maximum output at lower operating cost. Dynamically Balanced Impeller The impeller used in an ALmonard Exhaust Fan is of the propeller type and</p>			

		<p>since both hub and impeller are dynamically balances and frames and arms mounted on rubber bushing, vibration are virtually eliminated.</p> <p>With installation</p>			
33	AIR CURTAIN	<p>Size: 48" (L) Air Curtain is an environment, separation equipment which prevents outside air, insects and hot air entry to the conditioned area through the open door ways or the door being opened at frequent intervals. The principal of Air Curtain is that it blows the atmosphere air to constant velocity at the doorways and forms a Air stream for the entire width and height of the door openings. The velocity will vary depending on the effective throw of the air stream. Moreover, you can reduce your energy consumption considerably by holding the uniform cold air temperature at the air conditioned area. In Total it is an energy conservation unit for the air conditioned area. It also eliminated the flies and other small insects infiltration through an open door in order to maintain the required hygienic standard in the specified areas. Our commitment to quality at economical Rates had made millions to provide comfortable environment in their establishments. 1400 RPM, 1.5 HP MOTOR, 180Watt</p>			
34	INSECT KILLER	<p>DOUBLE TUB Dimension (cm): lxbxh - 65x10.8X30.3 8, 000 Hour lamp life with a high powered killing grid Wall mounted or no standing - hanging chain included Removable catchment tray for dead insect bodies, easily cleanable without insect contact,</p>			

		Electric power: 39 watts / bulbs: philips tubes 2 pcs 18 watt blue colour uv bulbs (replaceable)			
35	FRESH AIR VENT DIFFUSER	Size:-15"X6" ADJUSTABLE GRILLES This is the most common type of grille used as a supply outlet with adjustable vanes to provide multi directional air flow. Made out of extruded aluminium section and available in powder coated/anodised finish.			

Sign of the Bidder