## THE ODISHA STATE POLICE HOUSING & WELFARE CORPORATION LTD. JANAPATH, BHOINAGAR, BHUBANESWAR - 22

[Electrical Division]
Ph: 0674-2541545, 2542921, Fax: 0674-2541543
E-mail :- pmelectricalophwc2021@gmail.com, Website: www.ophwc.nic.in

## PRICE BID FOR THE WORK UNDER SL. NO :- 01 AS PER IFB

NAME OF THE WORK :- SUPPLY, INSTALLATION, TESTING & COMMISIONING OF FIRE FIGHTING & SUPRESSION SYSTEM AT HANDICAP GIRLS HOSTEL, RAJENDRA UNIVERSITY IN THE DISTRICT OF BOLANGIR.

BID REF NO :- 99/PM/ELECT/OPHWC/2022-23

NAME & ADDRESS OF

ADDRESS OF THE FIRM								
THE FIRM	Cost Summary							
SI.No	Description	Amount						
1	Fire External Hydrant System			iount	2,250.00			
2	Fire Extinguishers				43,900.00			
3	Fire Internal Hydrant System				1,11,800.00			
4	Fire Pump Room				3,42,701.00			
5	Signage							
Total Estimated C	ost excluding GST				5,00,651.00			
The cost of following	l ng works/ltems <b>not included</b> in above estimate;							
THE COST OF TOHOWIE	g works/items not included in above estimate,							
1	Over Head Tank - 5000 Litres							
2	Civil Works							
FIRE FIGHTING SYSTEM								
SL.NO	DESCRIPTION	UNIT	QTY	UNIT RATE	TOTAL AMOUNT			
	FIRE PUMP ROOM EQUIPMENT							
1.0	Supply, erection, testing & commissioning of electrical motor driven main pump of horizontal centrifugal end suction backpull out type with gland packing and capable to deliver 2280LPM at 70MWC. The pump shall be coupled to TEFC motor of suitable HP with speed of 2900 RPM and complete set shall mounted on common base frame. The quoted rate shall includes providing & fixing of coupling, coupling gaurd, etc.	No		3,15,000.00	-			
2.0	Supply, installation, testing & commissioning of diesel Engine driven common stand by pump, horizontal centrifugal end suction backpull out type with gland packing and capable to deliver 2280LPM at 70MWC. The pump shall coupled to suitable HP of Diesel engine radiator water cooled type with speed of 1800RPM and complete set shall be mounted on common base frame. Batteries & battery leads with stand, Fuel tank ( for 6 Hrs. operation ) with stand & gauge glass, Fuel piping with valves. The quoted rate shall includes radiator water cooling piping (if required) coupling gaurd and other stanadrd accessories.	No.		5,75,000.00	-			
3.0	Supply, erection, testing & commissioning of electrical motor driven Jockey pump of horizontal centrifugal end suction back pull out type with gland packing and capable to deliver 180LPM at 70MWC.The pump shall be coupled to TEFC motor of suitable HPwith speed of 2900RPM and complete set shall mounted on common base frame. The quoted rate shall includes providing & fixing of coupling, coupling gaurd etc	No.		1,18,000.00	-			
5.0	Supply, erection, testing & commissioning of electrical motor driven Booster pump with gland packing and capable to deliver 450LPM discharge, with weather proof control panel complete. The quoted rate shall includes providing & fixing of coupling, coupling gaurd etc.  Control Panel for Fire pumps.	No.	1.00	1,33,000.00	1,33,000.00			
3.0	Fabricating & Supply, installing, testing and commissioning of compartmentalised common control panel for Electrical motor driven pumps and Diesel engine driven pumps.	No.		2,03,000.00	ı			
b	Fabricating & Supply, installing, testing and commissioning of control panel for Terrace Pump.	No.	1.00	25,000.00	25,000.00			
6.0	1100 V GRADE POWER / CONTROL CABLES Supplying, laying, testing & commissioning of PVC outer sheath, steel armoured, aluminium / copper conductor, 1100v grade power cables with glands etc.The cables shall be laid in tray / Hume pipe / in trenches / on walls / floor etc. as required. For cables laid out door the rate shall exclude earth excavation providing brick and sand protection, refilling and compacting the earth.  95 sq.mm 3.5 Core Aluminium Cable (Main Pump)	Rmt		678.56	-			

	16 sq.mm 4 Core Aluminium Cable (For Jockey Pump)	Rmt		291.82	
	16 sq.mm 4 Core Aluminium Cable (For Booster Pump)	Rmt	50.00	291.82	14,591.00
d	1.5 sq.mm 12 Core copper Cable (Diesel Engine)	Rmt		403.00	-
7.0	CABLE TRAY				
	Supplying and fixing of perforated G.I.sheet cable tray with	Rmt		660.00	-
	neccessory angle iron suspension supports, anchor fasteners				
	etc. complete. Maximum height of suspension shall not exceed 500 mm.				
8.0		Rmt	50.00	245.00	12,250.00
6.0	G.I. Earthing strips of 50mm x 6mm thick, strip shall be run on floor / ceiling / walls, from the equipment to the nearest Earth pit	KIIIL	30.00	245.00	12,250.00
	with neccessory accessories as required. (Earth pit shall be				
	executed by other agencies).				
9.0	Supplying, installing, testing and commissioning of M.S. Pipes				
	confirming to IS 1239 Pt - I Heavy grade with painting, suitable				
	type of supports, anchor fasteners, bolts nuts, clamps, "U" bolt,				
	malleable specials such as Reducers, Tees, elbows, flanges.				
	Including cutting, Welding, fixing in / on walls, ceiling by using				
	suitable supports etc, as per drawings. The quoted rate shall also include for chasing / chipping walls, making bore holes in				
	walls / floor and making them good with filler material and				
	finished in cement morter etc. complete.				
	·				
	250mm nominal dia	Rmt		3,350.00	
	200mm nominal dia	Rmt		2,780.00	-
	150mm nominal dia	Rmt	45.00	2,332.00	
<u>0</u>	100mm nominal dia 80mm nominal dia	Rmt Rmt	15.00 10.00	1,884.00 1,370.00	28,260.00 13,700.00
10.0	Supplying, installing, testing and commissioning of ISI Mark	KIIIL	10.00	1,370.00	13,700.00
10.0	Dual Plate Wafer Type Non-return valves ( PN 16) with				
	required flanges, nuts, bolts and gaskets etc. complete				
а	150 mm nominal dia	Nos.		10,000.00	-
b	100 mm nominal dia for (Terrace )	Nos.	1.00	7,250.00	7,250.00
	80 mm nominal dia	Nos.		5,600.00	
11.0	Supplying, Installing, testing and commissioning ISI Mark CI				
	butterfly valves( PN 16) slim seal standared lever operated type				
	with required flanges, nuts, bolts etc. complete.	NI		40.500.00	
	250mm nominal dia (Tank Connection) 150mm nominal dia	Nos.		13,500.00 8,750.00	
	100mm nominal dia (For Terrace)	Nos.	2.00	6,850.00	13,700.00
	80mm nominal dia	Nos.		4,450.00	-
12.0	Supplying, Installing, testing and commissioning ISI Mark				
	Rubber Bellow with required flanges, nuts, bolts etc. complete.				
	150mm nominal dia	Nos.		8,300.00	-
	80mm nominal dia	Nos.		5,600.00	-
13.0	Supplying, installing and commissioning C.I.flanged "Y Srainer" with suitable flanges, nuts, bolts, gaskets etc. complete.				
	250mm dia.	Nos.		28,800.00	-
b	100mm dia.	Nos.	1.00	18,800.00	18,800.00
14.0	Supply and installation of Pressure switches of suitable range	Set	1.00	5,950.00	5,950.00
	(0 to 12 bar) for pumpsets with Fittings like Ball Valve unions / colors / reducers etc.				
15.0					
15.0	Supply and installation of Pressure gauges of suitable range (0-	Set	1.00	1,700.00	1,700.00
15.0	Supply and installation of Pressure gauges of suitable range (0- 16 bar), 100 mm diamter dial for pumpsets with Fittings like Ball	Set	1.00	1,700.00	1,700.00
	Supply and installation of Pressure gauges of suitable range (0- 16 bar), 100 mm diamter dial for pumpsets with Fittings like Ball Valve, Unions / colors / reducers etc.			·	·
15.0	Supply and installation of Pressure gauges of suitable range (0- 16 bar), 100 mm diamter dial for pumpsets with Fittings like Ball	Set Nos.	1.00	1,700.00	1,700.00 43,500.00
	Supply and installation of Pressure gauges of suitable range (0-16 bar), 100 mm diamter dial for pumpsets with Fittings like Ball Valve, Unions / colors / reducers etc.  Supplying and installation of Fire pressure vessel of 300mm dia and 2.0m high fabricated from 6-8 mm thick M.S. plate suitable for 10kg/sqcm. working pressure with accessories, painted with			·	·
	Supply and installation of Pressure gauges of suitable range (0-16 bar), 100 mm diamter dial for pumpsets with Fittings like Ball Valve, Unions / colors / reducers etc.  Supplying and installation of Fire pressure vessel of 300mm dia and 2.0m high fabricated from 6-8 mm thick M.S. plate suitable for 10kg/sqcm. working pressure with accessories, painted with two coats of Postal red enamel outside over a coat of primer for			·	
	Supply and installation of Pressure gauges of suitable range (0-16 bar), 100 mm diamter dial for pumpsets with Fittings like Ball Valve, Unions / colors / reducers etc.  Supplying and installation of Fire pressure vessel of 300mm dia and 2.0m high fabricated from 6-8 mm thick M.S. plate suitable for 10kg/sqcm. working pressure with accessories, painted with			·	·
16.0	Supply and installation of Pressure gauges of suitable range (0-16 bar), 100 mm diamter dial for pumpsets with Fittings like Ball Valve, Unions / colors / reducers etc. Supplying and installation of Fire pressure vessel of 300mm dia and 2.0m high fabricated from 6-8 mm thick M.S. plate suitable for 10kg/sqcm. working pressure with accessories, painted with two coats of Postal red enamel outside over a coat of primer for automatic operation of pump.			·	·
	Supply and installation of Pressure gauges of suitable range (0-16 bar), 100 mm diamter dial for pumpsets with Fittings like Ball Valve, Unions / colors / reducers etc.  Supplying and installation of Fire pressure vessel of 300mm dia and 2.0m high fabricated from 6-8 mm thick M.S. plate suitable for 10kg/sqcm. working pressure with accessories, painted with two coats of Postal red enamel outside over a coat of primer for automatic operation of pump.  Supplying & fixing MS Class 'C' diesel engine exhaust pipe duly			·	·
16.0	Supply and installation of Pressure gauges of suitable range (0-16 bar), 100 mm diamter dial for pumpsets with Fittings like Ball Valve, Unions / colors / reducers etc.  Supplying and installation of Fire pressure vessel of 300mm dia and 2.0m high fabricated from 6-8 mm thick M.S. plate suitable for 10kg/sqcm. working pressure with accessories, painted with two coats of Postal red enamel outside over a coat of primer for automatic operation of pump.  Supplying & fixing MS Class 'C' diesel engine exhaust pipe duly insulated with 50mm. thick glass wool with 1 mm, thick			·	·
16.0	Supply and installation of Pressure gauges of suitable range (0-16 bar), 100 mm diamter dial for pumpsets with Fittings like Ball Valve, Unions / colors / reducers etc.  Supplying and installation of Fire pressure vessel of 300mm dia and 2.0m high fabricated from 6-8 mm thick M.S. plate suitable for 10kg/sqcm. working pressure with accessories, painted with two coats of Postal red enamel outside over a coat of primer for automatic operation of pump.  Supplying & fixing MS Class 'C' diesel engine exhaust pipe duly			·	·
16.0	Supply and installation of Pressure gauges of suitable range (0-16 bar), 100 mm diamter dial for pumpsets with Fittings like Ball Valve, Unions / colors / reducers etc.  Supplying and installation of Fire pressure vessel of 300mm dia and 2.0m high fabricated from 6-8 mm thick M.S. plate suitable for 10kg/sqcm. working pressure with accessories, painted with two coats of Postal red enamel outside over a coat of primer for automatic operation of pump.  Supplying & fixing MS Class 'C' diesel engine exhaust pipe duly insulated with 50mm. thick glass wool with 1 mm, thick aluminium sheet cladding, residential silencer, including all fittings, clamps, steel support of suitable dia for the engine. The pipe shall be provided with 12 mm thick supercera ceramic fibre			·	·
17.0	Supply and installation of Pressure gauges of suitable range (0-16 bar), 100 mm diamter dial for pumpsets with Fittings like Ball Valve, Unions / colors / reducers etc.  Supplying and installation of Fire pressure vessel of 300mm dia and 2.0m high fabricated from 6-8 mm thick M.S. plate suitable for 10kg/sqcm. working pressure with accessories, painted with two coats of Postal red enamel outside over a coat of primer for automatic operation of pump.  Supplying & fixing MS Class 'C' diesel engine exhaust pipe duly insulated with 50mm. thick glass wool with 1 mm, thick aluminium sheet cladding, residential silencer,including all fittings, clamps, steel support of suitable dia for the engine. The pipe shall be provided with 12 mm thick supercera ceramic fibre rope.	Nos.		43,500.00	
16.0 17.0	Supply and installation of Pressure gauges of suitable range (0-16 bar), 100 mm diamter dial for pumpsets with Fittings like Ball Valve, Unions / colors / reducers etc.  Supplying and installation of Fire pressure vessel of 300mm dia and 2.0m high fabricated from 6-8 mm thick M.S. plate suitable for 10kg/sqcm. working pressure with accessories, painted with two coats of Postal red enamel outside over a coat of primer for automatic operation of pump.  Supplying & fixing MS Class 'C' diesel engine exhaust pipe duly insulated with 50mm. thick glass wool with 1 mm, thick aluminium sheet cladding, residential silencer,including all fittings, clamps, steel support of suitable dia for the engine. The pipe shall be provided with 12 mm thick supercera ceramic fibre rope.	Nos.		43,500.00	·
16.0 17.0 a 18.0	Supply and installation of Pressure gauges of suitable range (0-16 bar), 100 mm diamter dial for pumpsets with Fittings like Ball Valve, Unions / colors / reducers etc.  Supplying and installation of Fire pressure vessel of 300mm dia and 2.0m high fabricated from 6-8 mm thick M.S. plate suitable for 10kg/sqcm. working pressure with accessories, painted with two coats of Postal red enamel outside over a coat of primer for automatic operation of pump.  Supplying & fixing MS Class 'C' diesel engine exhaust pipe duly insulated with 50mm. thick glass wool with 1 mm, thick aluminium sheet cladding, residential silencer,including all fittings, clamps, steel support of suitable dia for the engine. The pipe shall be provided with 12 mm thick supercera ceramic fibre rope.  80mm dia  12V 10A Float Cum Boost Charger	Nos.  Rmt Nos.		43,500.00 2,000.00 9,500.00	
16.0 17.0 a 18.0 19.0	Supply and installation of Pressure gauges of suitable range (0-16 bar), 100 mm diamter dial for pumpsets with Fittings like Ball Valve, Unions / colors / reducers etc.  Supplying and installation of Fire pressure vessel of 300mm dia and 2.0m high fabricated from 6-8 mm thick M.S. plate suitable for 10kg/sqcm. working pressure with accessories, painted with two coats of Postal red enamel outside over a coat of primer for automatic operation of pump.  Supplying & fixing MS Class 'C' diesel engine exhaust pipe duly insulated with 50mm. thick glass wool with 1 mm, thick aluminium sheet cladding, residential silencer,including all fittings, clamps, steel support of suitable dia for the engine. The pipe shall be provided with 12 mm thick supercera ceramic fibre rope.	Nos.		43,500.00	·
16.0 17.0 a 18.0	Supply and installation of Pressure gauges of suitable range (0-16 bar), 100 mm diamter dial for pumpsets with Fittings like Ball Valve, Unions / colors / reducers etc.  Supplying and installation of Fire pressure vessel of 300mm dia and 2.0m high fabricated from 6-8 mm thick M.S. plate suitable for 10kg/sqcm. working pressure with accessories, painted with two coats of Postal red enamel outside over a coat of primer for automatic operation of pump.  Supplying & fixing MS Class 'C' diesel engine exhaust pipe duly insulated with 50mm. thick glass wool with 1 mm, thick aluminium sheet cladding, residential silencer, including all fittings, clamps, steel support of suitable dia for the engine. The pipe shall be provided with 12 mm thick supercera ceramic fibre rope.  80mm dia  12V 10A Float Cum Boost Charger  Anti Vibration Mounts  Supplying, installing, testing and commissioning of flow switch	Nos.  Rmt Nos.		43,500.00 2,000.00 9,500.00	
16.0 17.0 a 18.0 19.0	Supply and installation of Pressure gauges of suitable range (0-16 bar), 100 mm diamter dial for pumpsets with Fittings like Ball Valve, Unions / colors / reducers etc.  Supplying and installation of Fire pressure vessel of 300mm dia and 2.0m high fabricated from 6-8 mm thick M.S. plate suitable for 10kg/sqcm, working pressure with accessories, painted with two coats of Postal red enamel outside over a coat of primer for automatic operation of pump.  Supplying & fixing MS Class 'C' diesel engine exhaust pipe duly insulated with 50mm, thick glass wool with 1 mm, thick aluminium sheet cladding, residential silencer, including all fittings, clamps, steel support of suitable dia for the engine. The pipe shall be provided with 12 mm thick supercera ceramic fibre rope.  80mm dia  12V 10A Float Cum Boost Charger  Anti Vibration Mounts  Supplying, installing, testing and commissioning of flow switch (water flow detector), Flow switch shall have a paddle made of	Nos.  Rmt Nos.		43,500.00 2,000.00 9,500.00	
16.0 17.0 a 18.0 19.0	Supply and installation of Pressure gauges of suitable range (0-16 bar), 100 mm diamter dial for pumpsets with Fittings like Ball Valve, Unions / colors / reducers etc.  Supplying and installation of Fire pressure vessel of 300mm dia and 2.0m high fabricated from 6-8 mm thick M.S. plate suitable for 10kg/sqcm. working pressure with accessories, painted with two coats of Postal red enamel outside over a coat of primer for automatic operation of pump.  Supplying & fixing MS Class 'C' diesel engine exhaust pipe duly insulated with 50mm. thick glass wool with 1 mm, thick aluminium sheet cladding, residential silencer,including all fittings, clamps, steel support of suitable dia for the engine. The pipe shall be provided with 12 mm thick supercera ceramic fibre rope.  80mm dia  12V 10A Float Cum Boost Charger  Anti Vibration Mounts  Supplying, installing, testing and commissioning of flow switch (water flow detector), Flow switch shall have a paddle made of flexible material of the widthto fit within the pipe bore. The	Nos.  Rmt Nos.		43,500.00 2,000.00 9,500.00	
16.0 17.0 a 18.0 19.0	Supply and installation of Pressure gauges of suitable range (0-16 bar), 100 mm diamter dial for pumpsets with Fittings like Ball Valve, Unions / colors / reducers etc.  Supplying and installation of Fire pressure vessel of 300mm dia and 2.0m high fabricated from 6-8 mm thick M.S. plate suitable for 10kg/sqcm. working pressure with accessories, painted with two coats of Postal red enamel outside over a coat of primer for automatic operation of pump.  Supplying & fixing MS Class 'C' diesel engine exhaust pipe duly insulated with 50mm. thick glass wool with 1 mm, thick aluminium sheet cladding, residential silencer,including all fittings, clamps, steel support of suitable dia for the engine. The pipe shall be provided with 12 mm thick supercera ceramic fibre rope.  80mm dia  12V 10A Float Cum Boost Charger  Anti Vibration Mounts  Supplying, installing, testing and commissioning of flow switch (water flow detector), Flow switch shall have a paddle made of flexible material of the widtho fit within the pipe bore. The terminal box shall be mounted over the paddle/ pipe through a	Nos.  Rmt Nos.		43,500.00 2,000.00 9,500.00	
16.0 17.0 a 18.0 19.0	Supply and installation of Pressure gauges of suitable range (0-16 bar), 100 mm diamter dial for pumpsets with Fittings like Ball Valve, Unions / colors / reducers etc.  Supplying and installation of Fire pressure vessel of 300mm dia and 2.0m high fabricated from 6-8 mm thick M.S. plate suitable for 10kg/sqcm. working pressure with accessories, painted with two coats of Postal red enamel outside over a coat of primer for automatic operation of pump.  Supplying & fixing MS Class 'C' diesel engine exhaust pipe duly insulated with 50mm. thick glass wool with 1 mm, thick aluminium sheet cladding, residential silencer,including all fittings, clamps, steel support of suitable dia for the engine. The pipe shall be provided with 12 mm thick supercera ceramic fibre rope.  80mm dia  12V 10A Float Cum Boost Charger  Anti Vibration Mounts  Supplying, installing, testing and commissioning of flow switch (water flow detector), Flow switch shall have a paddle made of flexible material of the widthto fit within the pipe bore. The terminal box shall be mounted over the paddle/ pipe through a connecting socket. The switch shall be potential free in either	Nos.  Rmt Nos.		43,500.00 2,000.00 9,500.00	
16.0 17.0 a 18.0 19.0	Supply and installation of Pressure gauges of suitable range (0-16 bar), 100 mm diamter dial for pumpsets with Fittings like Ball Valve, Unions / colors / reducers etc.  Supplying and installation of Fire pressure vessel of 300mm dia and 2.0m high fabricated from 6-8 mm thick M.S. plate suitable for 10kg/sqcm. working pressure with accessories, painted with two coats of Postal red enamel outside over a coat of primer for automatic operation of pump.  Supplying & fixing MS Class 'C' diesel engine exhaust pipe duly insulated with 50mm. thick glass wool with 1 mm, thick aluminium sheet cladding, residential silencer,including all fittings, clamps, steel support of suitable dia for the engine. The pipe shall be provided with 12 mm thick supercera ceramic fibre rope.  80mm dia  12V 10A Float Cum Boost Charger  Anti Vibration Mounts  Supplying, installing, testing and commissioning of flow switch (water flow detector), Flow switch shall have a paddle made of flexible material of the widtho fit within the pipe bore. The terminal box shall be mounted over the paddle/ pipe through a	Nos.  Rmt Nos.		43,500.00 2,000.00 9,500.00	
16.0 17.0 a 18.0 19.0	Supply and installation of Pressure gauges of suitable range (0-16 bar), 100 mm diamter dial for pumpsets with Fittings like Ball Valve, Unions / colors / reducers etc.  Supplying and installation of Fire pressure vessel of 300mm dia and 2.0m high fabricated from 6-8 mm thick M.S. plate suitable for 10kg/sqcm. working pressure with accessories, painted with two coats of Postal red enamel outside over a coat of primer for automatic operation of pump.  Supplying & fixing MS Class 'C' diesel engine exhaust pipe duly insulated with 50mm. thick glass wool with 1 mm, thick aluminium sheet cladding, residential silencer,including all fittings, clamps, steel support of suitable dia for the engine. The pipe shall be provided with 12 mm thick supercera ceramic fibre rope.  80mm dia  12V 10A Float Cum Boost Charger  Anti Vibration Mounts  Supplying, installing, testing and commissioning of flow switch (water flow detector), Flow switch shall have a paddle made of flexible material of the widthlo fit within the pipe bore. The terminal box shall be mounted over the padele/ pipe through a connecting socket. The switch shall be potential free in either NO or NC position as required. The switch shall be able to trip and make/ break contact on the operation of a sprinkler head. The terminal box shall have connections for wiring to the Fire	Nos.  Rmt Nos.		43,500.00 2,000.00 9,500.00	·
16.0 17.0 a 18.0 19.0	Supply and installation of Pressure gauges of suitable range (0-16 bar), 100 mm diamter dial for pumpsets with Fittings like Ball Valve, Unions / colors / reducers etc.  Supplying and installation of Fire pressure vessel of 300mm dia and 2.0m high fabricated from 6-8 mm thick M.S. plate suitable for 10kg/sqcm. working pressure with accessories, painted with two coats of Postal red enamel outside over a coat of primer for automatic operation of pump.  Supplying & fixing MS Class 'C' diesel engine exhaust pipe duly insulated with 50mm. thick glass wool with 1 mm, thick aluminium sheet cladding, residential silencer,including all fittings, clamps, steel support of suitable dia for the engine. The pipe shall be provided with 12 mm thick supercera ceramic fibre rope.  80mm dia  12V 10A Float Cum Boost Charger  Anti Vibration Mounts  Supplying, installing, testing and commissioning of flow switch (water flow detector), Flow switch shall have a paddle made of flexible material of the widthlo fit within the pipe bore. The terminal box shall be mounted over the paddle/ pipe through a connecting socket. The switch shall be potential free in either NO or NC position as required. The switch shall be able to trip and make/ break contact on the operation of a sprinkler head. The terminal box shall have connections for wiring to the Fire alarm panel. The seat shall be of stainless steel. The flow	Nos.  Rmt Nos.		43,500.00 2,000.00 9,500.00	
16.0 17.0 a 18.0 19.0	Supply and installation of Pressure gauges of suitable range (0-16 bar), 100 mm diamter dial for pumpsets with Fittings like Ball Valve, Unions / colors / reducers etc.  Supplying and installation of Fire pressure vessel of 300mm dia and 2.0m high fabricated from 6-8 mm thick M.S. plate suitable for 10kg/sqcm. working pressure with accessories, painted with two coats of Postal red enamel outside over a coat of primer for automatic operation of pump.  Supplying & fixing MS Class 'C' diesel engine exhaust pipe duly insulated with 50mm. thick glass wool with 1 mm, thick aluminium sheet cladding, residential silencer,including all fittings, clamps, steel support of suitable dia for the engine. The pipe shall be provided with 12 mm thick supercera ceramic fibre rope.  80mm dia  12V 10A Float Cum Boost Charger  Anti Vibration Mounts  Supplying, installing, testing and commissioning of flow switch (water flow detector), Flow switch shall have a paddle made of flexible material of the widthlo fit within the pipe bore. The terminal box shall be mounted over the padele/ pipe through a connecting socket. The switch shall be potential free in either NO or NC position as required. The switch shall be able to trip and make/ break contact on the operation of a sprinkler head. The terminal box shall have connections for wiring to the Fire	Nos.  Rmt Nos.		43,500.00 2,000.00 9,500.00	
16.0 17.0 a 18.0 19.0	Supply and installation of Pressure gauges of suitable range (0-16 bar), 100 mm diamter dial for pumpsets with Fittings like Ball Valve, Unions / colors / reducers etc.  Supplying and installation of Fire pressure vessel of 300mm dia and 2.0m high fabricated from 6-8 mm thick M.S. plate suitable for 10kg/sqcm. working pressure with accessories, painted with two coats of Postal red enamel outside over a coat of primer for automatic operation of pump.  Supplying & fixing MS Class 'C' diesel engine exhaust pipe duly insulated with 50mm. thick glass wool with 1 mm, thick aluminium sheet cladding, residential silencer,including all fittings, clamps, steel support of suitable dia for the engine. The pipe shall be provided with 12 mm thick supercera ceramic fibre rope.  80mm dia  12V 10A Float Cum Boost Charger  Anti Vibration Mounts  Supplying, installing, testing and commissioning of flow switch (water flow detector) , Flow switch shall have a paddle made of flexible material of the widthto fit within the pipe bore. The terminal box shall be mounted over the paddle/ pipe through a connecting socket. The switch shall be potential free in either NO or NC position as required. The switch shall be able to trip and make/ break contact on the operation of a sprinkler head. The terminal box shall have connections for wiring to the Fire alarm panel. The seat shall be of stainless steel. The flow switch shall have IP: 55 protection.	Nos.  Rmt Nos.		43,500.00 2,000.00 9,500.00	·

	FIRE FIGHTING SYSTEM				
SL.NO	DESCRIPTION	UNIT	QTY	UNIT RATE	TOTAL
	EXTERNAL HYDRANT SYSTEM				7
	Supplying, installing, testing and commissioning of M.S Pipes				
	confirming to IS 1239 Pt - I Heavy grade with painting, suitable				
	type of supports ( Shall be fabricated by M.S. Channel / Angle /				
	Flat for above 50 mm dia), anchor fasteners, bolts nuts, clamps,				
4.0	"U" bolt, malleable specials such as Reducers,Tees, elbows,				
1.0	flanges. Including cutting, Welding, fixing in / on walls, ceiling by using suitable supports etc, as per drawings. The quoted				
	rate shall also include for chasing / chipping walls, making bore				
	holes in walls / floor and making them good with filler material				
	and finished in cement morter etc. complete.				
	·				
	a 150 mm dia External Hydrant	Mtr		2,332.00	
	b 100 mm dia (Terrace Ring Main)	Rmt		1,884.00	
	c 80 mm dia (Hydrant Post)	Rmt		1,370.00	
2.0	Supplying, Installing, testing and commissioning ISI Mark CI				
	butterfly valves( PN 16) slim seal standared lever operated type				
	with required flanges, nuts, bolts etc. complete				
	a 150mm nominal dia(For Ring Main and 4 Way )	Nos.		8,750.00	
3.0	Single headed hydrant valve as per IS 5290, made of S.S with	Nos.		5,780.00	
	63 mm dia instantaneous outlet of 80 mm dia fanged inlet				
	,Blank caps , chain and hand wheels etc complete.				
4.0	1 length of 15 M long, 63mm dia RRL hose with instataneuos	Nos.		4,550.00	
	couplings and Hoses shall be stored in side the hose cabinet.				
5.0	1 no. S.S short branch pipe with nozzle.	Nos.		2,165.00	
6.0	M.S. Hose Cabinet fabricated out of M.S. sheet of 16 swg. with	Nos.		4,000.00	
	glass fronted ( 4mm thick glass with rubber beeding) and size				
	of the Cabinet shall be 600 mm				
	(L)x450mm(H)x250mm(Width).Quoted rate shall be includes				
	Hinges, all fasteners etc, and Door shall be powder coated of				
	approved colour both inside and out side.				
7.0	Coating and wrapping of underground pipelines as per IS	Rmt		650.00	
	10221 : 2008 per running metre.		0.00	750.00	0.05
8.0	PCC Pedestal	Nos.	3.00	750.00	2,25
9.0	300 MM Hume Pipes as per IS standard	Rmt		600.00	
10.0	Earth Digging and Refilling and making good the same for	Rmt		100.00	
11.0	underground laying of Hydrant Pipe as per IS standard			40.000.00	
11.0	Supplying, installing and commissioning of fire brigade inlet	Nos.		10,300.00	
	inlet connection of 4 way with 4 nos. 63 mm dia. built - in Gun metal Non- return valves instantaneous coupling type arranged				
	on 150 mm dia. Pipe manifold and connected to wet riser main .				
L COST EXC					2,25
L GOO! LAG					
	FIRE FIGHTING SYSTEM		OTV	LIMIT DATE	TOTAL
SL.NO		UNIT	QTY	UNIT RATE	
	FIRE FIGHTING SYSTEM DESCRIPTION		QTY	UNIT RATE	
SL.NO	FIRE FIGHTING SYSTEM  DESCRIPTION  INTERNAL HYDRANT SYSTEM		QTY	UNIT RATE	
	FIRE FIGHTING SYSTEM  DESCRIPTION  INTERNAL HYDRANT SYSTEM  Supplying, installing, testing and commissioning of M.S Pipes		QTY	UNIT RATE	
SL.NO	FIRE FIGHTING SYSTEM  DESCRIPTION  INTERNAL HYDRANT SYSTEM  Supplying, installing, testing and commissioning of M.S Pipes confirming to IS 1239 Pt - I Medium grade with painting,		QTY	UNIT RATE	
SL.NO	FIRE FIGHTING SYSTEM  DESCRIPTION  INTERNAL HYDRANT SYSTEM  Supplying, installing, testing and commissioning of M.S Pipes		QTY	UNIT RATE	
SL.NO	FIRE FIGHTING SYSTEM  DESCRIPTION  INTERNAL HYDRANT SYSTEM  Supplying, installing, testing and commissioning of M.S Pipes confirming to IS 1239 Pt - I Medium grade with painting, suitable type of supports ( Shall be fabricated by M.S. Channel /		QTY	UNIT RATE	
SL.NO	FIRE FIGHTING SYSTEM  DESCRIPTION  INTERNAL HYDRANT SYSTEM  Supplying, installing, testing and commissioning of M.S Pipes confirming to IS 1239 Pt - I Medium grade with painting, suitable type of supports ( Shall be fabricated by M.S. Channel / Angle / Flat for above 50 mm dia), anchor fasteners, bolts nuts,		QTY	UNIT RATE	
SL.NO	FIRE FIGHTING SYSTEM  DESCRIPTION  INTERNAL HYDRANT SYSTEM  Supplying, installing, testing and commissioning of M.S Pipes confirming to IS 1239 Pt - I Medium grade with painting, suitable type of supports ( Shall be fabricated by M.S. Channel / Angle / Flat for above 50 mm dia), anchor fasteners, bolts nuts, clamps, "U" botte, malleable specials such as Reducers,Tees, elbows, flanges. Including cutting, Welding, fixing in / on walls, ceiling by using suitable supports etc, as per drawings. The		QTY	UNIT RATE	
SL.NO	FIRE FIGHTING SYSTEM  DESCRIPTION  INTERNAL HYDRANT SYSTEM  Supplying, installing, testing and commissioning of M.S Pipes confirming to IS 1239 Pt - I Medium grade with painting, suitable type of supports ( Shall be fabricated by M.S. Channel / Angle / Flat for above 50 mm dia), anchor fasteners, bolts nuts, clamps, "U" botte, malleable specials such as Reducers, Tees, elbows, flanges. Including cutting, Welding, fixing in / on walls, ceiling by using suitable supports etc, as per drawings. The quoted rate shall also include for chasing / chipping walls,		QTY	UNIT RATE	
SL.NO	INTERNAL HYDRANT SYSTEM  Supplying, installing, testing and commissioning of M.S Pipes confirming to IS 1239 Pt - I Medium grade with painting, suitable type of supports (Shall be fabricated by M.S. Channel / Angle / Flat for above 50 mm dia), anchor fasteners, bolts nuts, clamps, "U" bolte, malleable specials such as Reducers, Tees, elbows, flanges. Including cutting, Welding, fixing in / on walls, ceiling by using suitable supports etc, as per drawings. The quoted rate shall also include for chasing / chipping walls, making bore holes in walls / floor and making them good with		QTY	UNIT RATE	
SL.NO	FIRE FIGHTING SYSTEM  DESCRIPTION  INTERNAL HYDRANT SYSTEM  Supplying, installing, testing and commissioning of M.S Pipes confirming to IS 1239 Pt - I Medium grade with painting, suitable type of supports ( Shall be fabricated by M.S. Channel / Angle / Flat for above 50 mm dia), anchor fasteners, bolts nuts, clamps, "U" botte, malleable specials such as Reducers, Tees, elbows, flanges. Including cutting, Welding, fixing in / on walls, ceiling by using suitable supports etc, as per drawings. The quoted rate shall also include for chasing / chipping walls,		QTY	UNIT RATE	
<b>SL.NO</b>	FIRE FIGHTING SYSTEM  DESCRIPTION  INTERNAL HYDRANT SYSTEM  Supplying, installing, testing and commissioning of M.S Pipes confirming to IS 1239 Pt - I Medium grade with painting, suitable type of supports ( Shall be fabricated by M.S. Channel / Angle / Flat for above 50 mm dia), anchor fasteners, bolts nuts, clamps, "U" bolte, malleable specials such as Reducers,Tees, elbows, flanges. Including cutting, Welding, fixing in / on walls, ceiling by using suitable supports etc, as per drawings. The quoted rate shall also include for chasing / chipping walls, making bore holes in walls / floor and making them good with filler material and finished in cement morter etc. complete.	UNIT			AMOUN
1.0	INTERNAL HYDRANT SYSTEM  Supplying, installing, testing and commissioning of M.S Pipes confirming to IS 1239 Pt - I Medium grade with painting, suitable type of supports (Shall be fabricated by M.S. Channel / Angle / Flat for above 50 mm dia), anchor fasteners, bolts nuts, clamps, "U" bolte, malleable specials such as Reducers, Tees, elbows, flanges. Including cutting, Welding, fixing in / on walls, ceiling by using suitable supports etc, as per drawings. The quoted rate shall also include for chasing / chipping walls, making bore holes in walls / floor and making them good with filler material and finished in cement morter etc. complete.	UNIT	QTY 20.00	1,000.00	AMOUN
1.0	INTERNAL HYDRANT SYSTEM  Supplying, installing, testing and commissioning of M.S Pipes confirming to IS 1239 Pt - I Medium grade with painting, suitable type of supports ( Shall be fabricated by M.S. Channel / Angle / Flat for above 50 mm dia), anchor fasteners, bolts nuts, clamps, "U" botte, malleable specials such as Reducers, Tees, elbows, flanges. Including cutting, Welding, fixing in / on walls, ceiling by using suitable supports etc, as per drawings. The quoted rate shall also include for chasing / chipping walls, making bore holes in walls / floor and making them good with filler material and finished in cement morter etc. complete.	UNIT			AMOUN
1.0	FIRE FIGHTING SYSTEM  DESCRIPTION  INTERNAL HYDRANT SYSTEM  Supplying, installing, testing and commissioning of M.S Pipes confirming to IS 1239 Pt - I Medium grade with painting, suitable type of supports (Shall be fabricated by M.S. Channel / Angle / Flat for above 50 mm dia), anchor fasteners, bolts nuts, clamps, "U" bolte, malleable specials such as Reducers, Tees, elbows, flanges. Including cutting, Welding, fixing in / on walls, ceiling by using suitable supports etc, as per drawings. The quoted rate shall also include for chasing / chipping walls, making bore holes in walls / floor and making them good with filler material and finished in cement morter etc. complete.  a 100mm nominal dia b 80mm nominal dia Supplying, Installing, testing and commissioning ISI Mark CI	UNIT			AMOUN
1.0	INTERNAL HYDRANT SYSTEM  Supplying, installing, testing and commissioning of M.S Pipes confirming to IS 1239 Pt - I Medium grade with painting, suitable type of supports (Shall be fabricated by M.S. Channel / Angle / Flat for above 50 mm dia), anchor fasteners, bolts nuts, clamps, "U" bolte, malleable specials such as Reducers,Tees, elbows, flanges. Including cutting, Welding, fixing in / on walls, ceiling by using suitable supports etc, as per drawings. The quoted rate shall also include for chasing / chipping walls, making bore holes in walls / floor and making them good with filler material and finished in cement morter etc. complete.  a 100mm nominal dia  Bomm nominal dia  Supplying, Installing, testing and commissioning ISI Mark CI butterfly valves (PN 16) slim seal standared lever operated type	UNIT			AMOUN
1.0 2.0	INTERNAL HYDRANT SYSTEM  Supplying, installing, testing and commissioning of M.S Pipes confirming to IS 1239 Pt - I Medium grade with painting, suitable type of supports (Shall be fabricated by M.S. Channel / Angle / Flat for above 50 mm dia), anchor fasteners, bolts nuts, clamps, "U" bolte, malleable specials such as Reducers,Tees, elbows, flanges. Including cutting, Welding, fixing in / on walls, ceiling by using suitable supports etc, as per drawings. The quoted rate shall also include for chasing / chipping walls, making bore holes in walls / floor and making them good with filler material and finished in cement morter etc. complete.  a 100mm nominal dia b 80mm nominal dia Supplying, Installing, testing and commissioning ISI Mark CI butterfly valves (PN 16) slim seal standared lever operated type with required flanges, nuts, bolts etc. complete	Rmt Rmt	20.00	1,000.00	20,000
1.0 2.0	INTERNAL HYDRANT SYSTEM  Supplying, installing, testing and commissioning of M.S Pipes confirming to IS 1239 Pt - I Medium grade with painting, suitable type of supports (Shall be fabricated by M.S. Channel / Angle / Flat for above 50 mm dia), anchor fasteners, bolts nuts, clamps, "U" bolte, malleable specials such as Reducers,Tees, elbows, flanges. Including cutting, Welding, fixing in / on walls, ceiling by using suitable supports etc, as per drawings. The quoted rate shall also include for chasing / chipping walls, making bore holes in walls / floor and making them good with filler material and finished in cement morter etc. complete.  a 100mm nominal dia  Supplying, Installing, testing and commissioning ISI Mark CI butterfly valves(PN 16) slim seal standared lever operated type with required flanges, nuts, bolts etc. complete	Rmt Rmt Rmt	20.00	1,000.00	20,000 6,900
1.0 2.0	INTERNAL HYDRANT SYSTEM  Supplying, installing, testing and commissioning of M.S Pipes confirming to IS 1239 Pt - I Medium grade with painting, suitable type of supports (Shall be fabricated by M.S. Channel / Angle / Flat for above 50 mm dia), anchor fasteners, bolts nuts, clamps, "U" bolte, malleable specials such as Reducers,Tees, elbows, flanges. Including cutting, Welding, fixing in / on walls, ceiling by using suitable supports etc, as per drawings. The quoted rate shall also include for chasing / chipping walls, making bore holes in walls / floor and making them good with filler material and finished in cement morter etc. complete.  a 100mm nominal dia b 80mm nominal dia Supplying, Installing, testing and commissioning ISI Mark CI butterfly valves (PN 16) slim seal standared lever operated type with required flanges, nuts, bolts etc. complete	Rmt Rmt	20.00	1,000.00	20,000
1.0 2.0	DESCRIPTION  INTERNAL HYDRANT SYSTEM  Supplying, installing, testing and commissioning of M.S Pipes confirming to IS 1239 Pt - I Medium grade with painting, suitable type of supports (Shall be fabricated by M.S. Channel / Angle / Flat for above 50 mm dia), anchor fasteners, bolts nuts, clamps, "U" bolte, malleable specials such as Reducers, Tees, elbows, flanges. Including cutting, Welding, fixing in / on walls, ceiling by using suitable supports etc, as per drawings. The quoted rate shall also include for chasing / chipping walls, making bore holes in walls / floor and making them good with filler material and finished in cement morter etc. complete.  a 100mm nominal dia b 80mm nominal dia Supplying, Installing, testing and commissioning ISI Mark CI butterfly valves (PN 16) slim seal standared lever operated type with required flanges, nuts, bolts etc. complete a 100mm nominal dia Single headed hydrant valve as per IS 5290, made of S.S with	Rmt Rmt Rmt	20.00	1,000.00	20,000 6,900
2.0 3.0	FIRE FIGHTING SYSTEM  DESCRIPTION  INTERNAL HYDRANT SYSTEM  Supplying, installing, testing and commissioning of M.S Pipes confirming to IS 1239 Pt - I Medium grade with painting, suitable type of supports ( Shall be fabricated by M.S. Channel / Angle / Flat for above 50 mm dia), anchor fasteners, bolts nuts, clamps, "U" bolte, malleable specials such as Reducers, Tees, elbows, flanges. Including cutting, Welding, fixing in / on walls, ceiling by using suitable supports etc, as per drawings. The quoted rate shall also include for chasing / chipping walls, making bore holes in walls / floor and making them good with filler material and finished in cement morter etc. complete.  a 100mm nominal dia  Supplying, Installing, testing and commissioning ISI Mark CI butterfly valves( PN 16) slim seal standared lever operated type with required flanges, nuts, bolts etc. complete  100mm nominal dia  Single headed hydrant valve as per IS 5290, made of S.S with 63 mm dia instantaneous outletof 80 mm dia fanged inelt ,Blank caps , chain and hand wheels etc complete.	Rmt Rmt Nos. Nos.	20.00 1.00 2.00	1,000.00 6,900.00 5,780.00	20,000 6,900 11,560
1.0 2.0	INTERNAL HYDRANT SYSTEM  Supplying, installing, testing and commissioning of M.S Pipes confirming to IS 1239 Pt - I Medium grade with painting, suitable type of supports (Shall be fabricated by M.S. Channel / Angle / Flat for above 50 mm dia), anchor fasteners, bolts nuts, clamps, "U" bolte, malleable specials such as Reducers,Tees, elbows, flanges. Including cutting, Welding, fixing in / on walls, ceiling by using suitable supports etc, as per drawings. The quoted rate shall also include for chasing / chipping walls, making bore holes in walls / floor and making them good with filler material and finished in cement morter etc. complete.  a 100mm nominal dia b 80mm nominal dia b 80mm nominal dia Supplying, Installing, testing and commissioning ISI Mark CI butterfly valves(PN 16) slim seal standared lever operated type with required flanges, nuts, bolts etc. complete a 100mm nominal dia Single headed hydrant valve as per IS 5290, made of S.S with 63 mm dia instantaneous outletof 80 mm dia fanged inelt ,Blank	Rmt Rmt Rmt	20.00	1,000.00	20,000 6,900
2.0 3.0	INTERNAL HYDRANT SYSTEM  Supplying, installing, testing and commissioning of M.S Pipes confirming to IS 1239 Pt - I Medium grade with painting, suitable type of supports (Shall be fabricated by M.S. Channel / Angle / Flat for above 50 mm dia), anchor fasteners, bolts nuts, clamps, "U" bolte, malleable specials such as Reducers,Tees, elbows, flanges. Including cutting, Welding, fixing in / on walls, ceiling by using suitable supports etc, as per drawings. The quoted rate shall also include for chasing / chipping walls, making bore holes in walls / floor and making them good with filler material and finished in cement morter etc. complete.  a 100mm nominal dia  Supplying, Installing, testing and commissioning ISI Mark CI butterfly valves(PN 16) slim seal standared lever operated type with required flanges, nuts, bolts etc. complete  a 100mm nominal dia  Single headed hydrant valve as per IS 5290, made of S.S with 63 mm dia instantaneous outletof 80 mm dia fanged inelt ,Blank caps , chain and hand wheels etc complete	Rmt Rmt Nos. Nos.	20.00 1.00 2.00	1,000.00 6,900.00 5,780.00	20,000 6,900 11,566
2.0 3.0	INTERNAL HYDRANT SYSTEM  Supplying, installing, testing and commissioning of M.S Pipes confirming to IS 1239 Pt - I Medium grade with painting, suitable type of supports (Shall be fabricated by M.S. Channel / Angle / Flat for above 50 mm dia), anchor fasteners, bolts nuts, clamps, "U" bolte, malleable specials such as Reducers,Tees, elbows, flanges. Including cutting, Welding, fixing in / on walls, ceiling by using suitable supports etc, as per drawings. The quoted rate shall also include for chasing / chipping walls, making bore holes in walls / floor and making them good with filler material and finished in cement morter etc. complete.  a 100mm nominal dia  Supplying, Installing, testing and commissioning ISI Mark CI butterfly valves(PN 16) slim seal standared lever operated type with required flanges, nuts, bolts etc. complete  a 100mm nominal dia  Single headed hydrant valve as per IS 5290, made of S.S with 63 mm dia instantaneous outletof 80 mm dia fanged inelt ,Blank caps , chain and hand wheels etc complete	Rmt Rmt Nos. Nos.	20.00 1.00 2.00	1,000.00 6,900.00 5,780.00	20,000 6,900 11,566
2.0 3.0	INTERNAL HYDRANT SYSTEM  Supplying, installing, testing and commissioning of M.S Pipes confirming to IS 1239 Pt - I Medium grade with painting, suitable type of supports (Shall be fabricated by M.S. Channel / Angle / Flat for above 50 mm dia), anchor fasteners, bolts nuts, clamps, "U" bolte, malleable specials such as Reducers,Tees, elbows, flanges. Including cutting, Welding, fixing in / on walls, ceiling by using suitable supports etc, as per drawings. The quoted rate shall also include for chasing / chipping walls, making bore holes in walls / floor and making them good with filler material and finished in cement morter etc. complete.  a 100mm nominal dia  Supplying, Installing, testing and commissioning ISI Mark CI butterfly valves(PN 16) slim seal standared lever operated type with required flanges, nuts, bolts etc. complete  a 100mm nominal dia  Single headed hydrant valve as per IS 5290, made of S.S with 63 mm dia instantaneous outletof 80 mm dia fanged inelt ,Blank caps , chain and hand wheels etc complete	Rmt Rmt Nos. Nos.	20.00 1.00 2.00	1,000.00 6,900.00 5,780.00	20,000 6,900 11,560
2.0 3.0 4.0	INTERNAL HYDRANT SYSTEM  Supplying, installing, testing and commissioning of M.S Pipes confirming to IS 1239 Pt - I Medium grade with painting, suitable type of supports (Shall be fabricated by M.S. Channel / Angle / Flat for above 50 mm dia), anchor fasteners, bolts nuts, clamps, "U" bolte, malleable specials such as Reducers, Tees, elbows, flanges. Including cutting, Welding, fixing in / on walls, ceiling by using suitable supports etc, as per drawings. The quoted rate shall also include for chasing / chipping walls, making bore holes in walls / floor and making them good with filler material and finished in cement morter etc. complete.  a 100mm nominal dia b 80mm nominal dia b 80mm nominal dia Supplying, Installing, testing and commissioning ISI Mark CI butterfly valves (PN 16) slim seal standared lever operated type with required flanges, nuts, bolts etc. complete a 100mm nominal dia Single headed hydrant valve as per IS 5290, made of S.S with 63 mm dia instantaneous outletof 80 mm dia fanged inelt, Blank caps, chain and hand wheels etc complete  1 lengths of 15 M long, 63mm dia RRL hose with instataneuos couplings and Hoses shall be stored in side the hose cabinet.	Rmt Rmt Nos. Nos.	20.00 1.00 2.00	1,000.00 6,900.00 5,780.00 4,550.00	20,000 6,900 11,560

7.0	M.S. Hose Cabinet fabricated out of M.S. sheet of 16 swg. with glass fronted ( 4mm thick glass with rubber beeding) and size of the Cabinet shall be 600 mm (L)x450mm(H)x250mm(Width).Quoted rate shall be includes Hinges, all fasteners etc, and Door shall be powder coated of approved colour both inside and out side.	Nos.	2.00	10,700.00	21,400.00
8.0	Supplying and installation of Fire Air vessel of 150mm dia and 1m high fabricated from 6-8 mm thick M.S. plate suitable for 10kg/sqcm. working pressure with accessories, painted with two coats of Postal red enamel outside over a coat of primer	Nos.	1.00	15,300.00	15,300.00
9.0	Supplying, installing and commissioning of fire brigade inlet connection of 2 way with 2nos. 63 mm dia. built - in Gun metal Non- return valves instantaneous coupling type arranged on 150 mm dia. Pipe manifold and connected to wet riser main . Qouted rate shall be included with C.I. Butterfly valve, complete.	Nos.	1.00	7,650.00	7,650.00
10.0	Supplying, installing, testing and commissioning of Gun metal /Brass Forged chrome finished Ball valves with fittings of screwed end type.			-	-
	a 25mm dia.(For hose reel)	Nos.	2.00	1,180.00	2,360.00
TOTAL COST EXC					1,11,800.00
SL.NO	FIRE FIGHTING SYSTE DESCRIPTION	UNIT	QTY	UNIT RATE	TOTAL
SL.NO	DESCRIPTION	ONT	QII	ONITRATE	AMOUNT
	EXTINGUISHERS				
1.0	Supply installation testing and commissioning of Clean Agent 2 Itrs capacitry Fire Extinguisher with initial charge complete with wall fixing bracket. The extinguisher shall conform to IS 940 and have certification mark engraved.	Nos	2	8,500.00	17,000.00
2.0	Supply installation testing and commissioning of CO2 4.5kg capacitry Fire Extinguisher made from seamless steel cylinder with initial charge complete with wall fixing bracket. The extinguisher shalconform to IS 2878 and have certification mark engraved.	Nos	2	6,500.00	13,000.00
3.0	Supply and installation testing and commissioning of DCP 6kg capacitry Fire Extinguisher with brass forging cap, 120 Gms CO2 gas cartridge inner container, hose and plain nozzle supplied with initial charge complete with wall fixing bracket. The extinguisher shall conform to IS 2171 and have certificate mark engraved.	Nos	2	4,000.00	8,000.00
4.0	Supply installation testing and commissioning of Mechanical foam type 9 ltrs capacitry Fire Extinguisher (AFFFConcentrate)	Nos	1	4,000.00	4,000.00
	Supply of Fire Buckets	Nos	1	1,900.00	1,900.00
TOTAL COST EXC					43,900.00
	Total Rs.				500651.00
	Total Estimated Cost in Figures				500651.00 5,00,651.00
	Total Estimated Cost in Figures				5,00,651.00
EXCESS	LESS (Please Tick)			%	
	Quoted Amount in Figure				
	Quoted Amount in words				

N:B- The Estimated cost is exclusive of GST .

Signature of Tenderer with seal

Sd/-Asst. Project Manager[Elect.] Sd/-APM (Elect.) Hqr.

Sd/-Project Manager(Elect.)